


STANAG LEVEL 1



Protection Level 1
according to **STANAG 4569 standard**

Designed for the following threats:

7.62 × 51 NATO BALL (BALL M80), with a velocity of 833 m/s at 30 meters.

5.56 × 45 NATO M193, with a velocity of 937 m/s at 30 meters.

Fire resistance according to EN 13087-7:2000 standard and flame resistance according to FED-STD-191 standard, method 5905.1.

The ballistic panels withstand, without prejudice of their ballistic protection properties, temperatures between -37 °C and +51 °C and submersion in salt water for a minimum period of 3 hours in 1 meter in depth.

The ballistic panels have high resistance to corrosion caused by diesel, gasoline, motor oil, hydraulic fluids, JP-8 aviation fuel, oil for cleaning and maintenance of weapons, insect repellent and facial paint.

Ballistic panel with the possibility of incorporating a decorative phenolic according to the customer's preferences.

These rigid panels take in consideration new developments in different areas, namely multi-scale materials with high energy absorption.

The ballistic panels are covered with 10 years guarantee.



**BEYOND
COMPOSITE**

SONAE Campus
Lugar do Espido, Via Norte
4470-177 Maia
Portugal

www.beyondcomposite.com
geral@beyondcomposite.com
+351 221 104 798

Properties	Obtained Values
Weight (Kg/m ²)	20
Thickness (mm)	19